

2-Part Epoxy Thinner**SECTION 1: IDENTIFICATION**

Product Identifier:	2-Part Epoxy Thinner
Other Means of Identification:	6050 Catalyst
Part Number:	
Recommended Use:	Adhesive Thinner
Restrictions on Use:	None known
Supplier Identifier:	Sterling Marking Products Inc., 1147 Gainsborough Road, London, ON Canada N6H 5L5 1-800-265-5957, 519-434-5785
Emergency Phone Number:	CANUTEC (613) 966-6666, Cellular *666

SECTION 2: HAZARD IDENTIFICATION

Classified according to Canada's Hazardous Products Regulations (WHMIS 2015) and the U.S. Hazardous Communication Standard (HCS 2012)

Class B, Division 3 - Combustible Liquid

Class D, Division 2B - Skin/Eye Irritant



Signal Word: Danger

Hazard Statements:

Combustible Liquid

May cause Drowsiness or Dizziness

Causes Eye Irritation

Causes Skin Irritation

Precautionary Statements:

Use only out of doors or in a well-ventilated area

Keep container tightly closed

Keep away from heat, hot surfaces, sparks, open flames or other ignition sources. No smoking.

Avoid breathing vapours

Wear protective gloves and eye protection

Wash hands and skin thoroughly after handling

Supplementary Precautionary Statements:

Ground/bond container and receiving equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapours/spray.

In case of fire: Use foam, carbon dioxide, dry powder or water fog for extinction.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Call a POISON CENTER or doctor/physician if you feel unwell.

Dispose of contents/container in accordance with local regulations.

Supplemental label information

Repeated exposure may cause skin dryness or cracking.

If in eyes, flush eyes thoroughly with water for several minutes. Remove contact lenses after the initial 1-2 minutes and continue flushing for several additional minutes. If effects occur consult a physician, preferably an ophthalmologist. If ingested, there is no specific antidote. Do not induce vomiting. Seek prompt medical attention.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS		
Component	CAS Registry	Concentration % (w/w)
Ethylene Glycol Butyl Ether	111-76-2	100%

Note: All ingredients are listed on the Domestic Substances List (DSL) and the Toxic Substances Control Act (TSCA) list.

This product contains organic solvents.

SECTION 4: FIRST AID MEASURES

General information.

NOTE! Keep affected person away from heat, sparks and flames!

Inhalation:

Move the exposed person to fresh air at once. Perform artificial respiration if breathing has stopped. Keep the affected person warm and at rest. Get prompt medical attention.

Ingestion:

NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! DO NOT INDUCE VOMITING! Get medical attention immediately!

Skin contact:

Remove affected person from source of contamination. Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

Eye contact:

Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Immediately transport to hospital or eye specialist.

Most important symptoms and effects, both acute and delayed.

General information:

The severity of the symptoms described will vary dependent of the concentration and the length of exposure.

Inhalation:

Vapours may cause headache, fatigue, dizziness and nausea.

Ingestion:

May cause nausea, headache, dizziness and intoxication.

Skin contact:

Prolonged contact may cause redness, irritation and dry skin.

Eye contact:

May cause severe irritation to eyes.

Indication of any immediate medical attention and special treatment needed:

No recommendation given, but first aid may still be required in case of accidental exposure, inhalation or ingestion of this chemical. If in doubt, GET MEDICAL ATTENTION PROMPTLY!

Notes to Physician: No specific antidote. Treatment based on sound judgement of physician and individual reactions of patient. First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection).

SECTION 5: FIRE-FIGHTING MEASURES

Flammability: Flammable Flash Point (°C TCC): ~67.22

Hazardous Combustion Products: Oxides of carbon, oxides of nitrogen, and other organic combustion products.

Potential Hazards: HIGHLY FLAMMABLE: Will be easily ignited by heat, sparks or flames. Vapours may form explosive mixtures with air. Vapours may travel to source of ignition and flash back. Most vapours are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapour explosion hazard indoors, outdoors or in sewers. Runoff to sewer may create fire or explosion hazard. Containers may explode when heated.

Means of Extinction Fire: CAUTION: This product has a low flash point: Use of water spray when fighting fire may be inefficient. Dry chemical, carbon dioxide, water spray or alcohol-resistant foam. Use media suitable for surrounding fire. Plan fire protection and response strategy through consultation with local fire protection authorities or appropriate specialists.

Special Fire-Fighting Procedures: Clear area of unprotected personnel. Firefighters should wear NIOSH-approved, self-contained breathing apparatus (SCBA). Use water spray to cool fire-exposed surfaces. Also, use water to flush spilled material away from source. Vapours are harmful; stay upwind of a fire to minimize breathing of vapours, gases, fumes, or decomposition products being generated.

Unusual Fire & Explosion Hazards: Containers exposed to intense heat from fire must be cooled to prevent vapour pressure build-up that may result in container rupture. Cool containers exposed directly to flames with large quantities of water as needed to prevent weakening of container itself. Never use a welding or cutting torch on or near container.

Empty Container Warning: “Empty” containers contain residues (liquid, solid, and/or vapour) that can be **dangerous**.

DO NOT pressurize, cut, weld, braze, grind, drill, solder, or expose containers to heat, sparks, open flame. They may explode and cause injury and/or death. **DO NOT** attempt to clean drums. Residues are difficult to remove. “Empty” drums should be completely drained, properly bunged and promptly returned to a drum re-conditioner. Dispose of all containers in an environmentally safe way and in accordance with governmental regulations. For work on tasks, refer to OSHA regulations ANSIZ49.1 and other governmental and industrial references pertaining to cleaning, repairing, welding, or other operations.

SECTION 6: ACCIDENTAL RELEASE MEASURES**Personal Precautionary Measures:**

Wear appropriate protective equipment.

Environmental Precautionary Measures:

Prevent entry into sewers or streams, dike if needed.

Methods and material for containment and cleaning up:

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Clean-up personnel should use respiratory and/or liquid contact protection.

Runoff or release to sewer, waterway or ground is forbidden.

Small Spillages: Collect with absorbent, non-combustible material into suitable containers.

Large Spillages: Absorb in vermiculite or dry sand and dispose of at a licensed hazardous waste collection point.

Inform Authorities if large amounts are involved.

SECTION 7. HANDLING AND STORAGE

Precautions for Safe Handling:

Flammable. Keep away from heat, sparks and flame. Avoid contact with eyes, skin and clothing. Avoid breathing vapour. Keep the containers closed when not in use. Use with adequate ventilation. Never use air pressure for transferring product. No smoking or open flame in storage, use or handling areas. Ensure proper electrical grounding procedures are in place. Use non-sparking tools. Containers, even those that have been emptied, will retain product residue and vapour and should be handled as if they were full until they have been cleaned. This product is a poor conductor of electricity and can become electrostatically charged during handling and use (for example: during mixing, filtering or pumping). If this charge reaches a sufficiently high level, static discharges or sparks capable of causing ignition might occur. Risk of vapour concentration on the floor and in low-lying areas.

Conditions for Safe Storage:

Store in a cool, dry, well-ventilated area, away from heat and ignition sources. Use explosion-proof ventilation to prevent vapour accumulation. Keep containers tightly closed. Store in original container. Store in accordance with good industrial practice.

SECTION 8: EXPOSURE CONTROL/PERSONAL PROTECTION

Control Parameters

SECTION II - HAZARDOUS INGREDIENTS			
Component	CAS Registry	Toxicology	Concentration % (w/w)
Ethylene Glycol Butyl Ether	112-76-2	ACGIH TLV-20 ppm; OSHA PEL 50 ppm	100%

Appropriate Engineering Controls:

Local exhaust ventilation as necessary to maintain exposure to within acceptable limits.

Personal Protective Equipment

Respiratory Protection: If exposure exceeds occupational exposure limits, use an appropriate NIOSH-approved respirator. For concentrations exceeding the recommended exposure limit, use NIOSH-approved air purifying respirator.

Gloves: Use gloves chemically resistant to this material. **NOTICE:** the selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials as well as the instructions/specifications provided by the glove supplier.

Skin Protection: The selection of personal protective equipment varies depending upon conditions of use. Skin contact should be prevented through use of suitable protective clothing, gloves and footwear, selected for conditions of use and exposure potential. Consideration must be given both to durability as well as permeation resistance. Impervious clothing. Impervious boots.

Eyes: Chemical goggles; also wear a face shield if splashing hazard exists.

Environmental Exposure Controls: Keep container tightly sealed when not in use.

Other Personal Protection Data: Ensure that eyewash stations and safety showers are proximal to the work station location.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Liquid.
Colour: Clear
Odor: Alcohol-like
pH: Not available.
Boiling Point: Not Available
Solubility: Miscible.
Flash Point (°C): 67.22°C
Auto-Ignition Temperature: Not Available
Other: Not available.

SECTION 10: STABILITY AND REACTIVITY

Reactivity:
 Not reactive.
Chemical Stability:
 Stable.
Hazardous Polymerization:
 Not Available.
Conditions to Avoid:
 Product can oxidize at elevated temperatures. Avoid contact with strong oxidizers. Avoid contact with heat, sparks, open flame and static discharge.
Materials to Avoid:
 Oxidizing materials. Strong acids or bases.
Hazardous Decomposition Products:
 Decomposition products can include and are not limited to: Carbon monoxide. Carbon dioxide.
Additional Information:
 No additional remarks.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on toxicological effects.
Toxicological information:
Acute toxicity:

Control Parameters

SECTION II - HAZARDOUS INGREDIENTS

Component	CAS Registry	Toxicology	Concentration % (w/w)
Ethylene Glycol Butyl Ether	112-76-2	ACGIH TLV-20 ppm; OSHA PEL 50 ppm	100%

Routes of Entry: Eye, Skin, Inhalation, Ingestion
Effects of Acute Exposure:
Eye: Inhalation or contact with material may irritate or burn skin and eyes.

Skin: Inhalation or contact with material may irritate or burn skin and eyes. May cause toxic effects if inhaled or absorbed through the skin.

Irritancy: Hazardous by WHMIS criteria

Carcinogenicity: Ethylene Glycol Butyl Ether is classified as IARC Group 3 (The International Agency for Research on Cancer) or Unclassifiable as Carcinogenic to Humans [CAS #108-88-3]. No components of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP or OSHA.

Teratogenicity: Insufficient data available.

Mutagenicity: Insufficient data available.

Medical Symptoms:

NERVOUS SYSTEM.

Drowsiness, dizziness, disorientation, vertigo. Mild intoxication (incl. fatigue, lassitude, irritability, headache, nausea).

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity:

No data on possible environmental effects have been found.

Toxicity:

Acute Fish Toxicity:

Avoid discharge to the aquatic environment.

Persistence and degradability:

Degradability:

There are no data on the degradability of this product.

Bioaccumulative potential:

Bioaccumulative potential:

No data available on bioaccumulation.

Mobility in soil:

Mobility:

The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces.

Other adverse effects:

Not determined

SECTION 13: DISPOSAL CONSIDERATIONS

General information:

Waste is classified as hazardous waste. Disposal to licensed waste disposal site in accordance with the local Waste Disposal Authority.

Waste treatment methods:

Dispose of waste and residues in accordance with local authority requirements.

SECTION 14: TRANSPORT INFORMATION

IATA Shipping (Air):

Adhesive Thinner

Packaging Instruction for Limited Quantity: Y344

Maximum Net Quantity (per outer package): 10L

Refer to Pkg. Inst. No. for inner packaging type and maximum quantity per inner package. DGR – 54th edition.

TDG Shipping Information: Not Regulated

WHMIS Classification:

Class B, Division 2 - Flammable Liquids

Class D, Division 2B - Skin/Eye Irritant

SECTION 15: REGULATORY INFORMATION**Chemical Safety Assessment**

No chemical safety assessment has been carried out.

WHMIS Hazardous Class:

B2 FLAMMABLE LIQUIDS

**SECTION 16: OTHER INFORMATION**

Additional Information: This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the SDS contains all the information required by the CPR.

Risk Phrases In Full:

R11 Highly flammable

R36 Irritating to eyes.

R67 Vapours may cause drowsiness and dizziness.

R66 Repeated exposure may cause skin dryness or cracking.

Hazard Statements In Full:

H319 Causes serious eye irritation.

H225 Highly flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

Disclaimer: NOTICE TO READER: Sterling Marking Products Inc. disclaims all express or implied warranties of merchantability and fitness for a particular purpose, with respect to the product or the information provided herein, and shall under no circumstances be liable for incidental or consequential damages.

Do not use ingredient information and/or ingredient percentages in this SDS as a product specification. For product specification information refer to a Product Specification Sheet and/or a Certificate of Analysis. These can be obtained from your local Sterling Marking Products Inc. Sales Office.

All information appearing herein is based upon data obtained from the manufacturer and/or recognized technical sources. While the information is believed to be correct, Sterling Marking Products Inc. makes no representations as to its accuracy or sufficiency. Conditions of use are beyond Sterling Marking Products' control and therefore users are responsible to verify this data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all risks of their use, handling, and disposal of the product, or from the publication or use of, reliance upon, information contained herein. This information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.

End of SDS.