

Part Number(s): TP9000

MATERIAL SAFETY DATA SHEET

SECTION I - MATERIAL IDENTIFICATION AND USE

Material Name Identifier:

Tampastar TPR

(TPR 191)

Supplier Name: Sterling Marking Products Inc.
 Street Address: 349 Ridout St. N.,
 City and Province: London, Ontario
 Postal Code: N6A 2N8

Telephone Numbers: (519) 434-5785, (800) 265-5957
 Fax Number: (519) 434-9516, (800) 667-6600
 Webpage: <http://www.sterling.ca>
 E-Mail: sales@sterling.ca

Emergency Telephone Number: CANUTEC (613) 996-6666; Cellular *666

Material Use: **Pad Printing Ink**

TDG Shipping Information:

PAINT, UN1263 Class: 3 PG: III

WHMIS Classification:

Class B, Division 3 – Combustible Liquid
 Class D, Division 2A – Very Chronically Toxic
 Class D, Division 2B – Skin/Eye Irritant

IATA Shipping (Air):

PAINT
Packaging Instruction for Limited Quantity: Y344
Maximum Net Quantity (per outer package): 10L
 Refer to Pkg. Inst. No. for inner packaging type and maximum quantity per inner package. DGR – 54th edition

SECTION II - HAZARDOUS INGREDIENTS

Component	CAS Registry	Toxicology	Concentration % (w/w)
Butylglycolate	7397-62-8	TLV: Not Available L _D 50: Not Available L _C 50: Not Available	1-5
Solvent Naptha	64742-95-6	TLV: Not Available L _D 50: 8400 mg/kg (oral, rat) L _C 50: Not Available	5-10
Cyclohexanone	108-94-1	ACGIH TLV-TWA 20 ppm;STEL 50 ppm (skin) L _D 50: 1800 mg/kg (oral, rat) L _C 50: 19000 mg/m3 (inhalation, rat)	5-10
Butylglycol Acetate	112-07-02	TLV: Not Available L _D 50: Not Available L _C 50: Not Available	10-15
4-Hydroxy-4-methyl-pentane-2-one	123-42-2	ACGIH TLV-TWA 50 ppm, STEL – 75 ppm L _D 50: 2520 mg/kg L _C 50: Not Available	30-35
Naptha (petroleum), Hydrotreated heavy	64742-48-9	TLV: Not Available L _D 50: Not Available L _C 50: Not Available	1-5

Note: All ingredients are listed on the Domestic Substances List (DSL) and the Toxic Substances Control Act (TSCA) list.



SECTION III - PHYSICAL DATA

<p>Physical State: Liquid Specific Gravity: Not available Colour: colour depending on ink Viscosity 20°C: >150 seconds DIN-cup 4mm Vapour Pressure(20 °C): 3 hPa Evaporation Rate : slower vs. Butylacetate</p>	<p>% Volatile: Not available Boiling Point (°C): 153 (initial) Odour: Like solvent Solubility in Water (20 °C): Parts of solvent Flash Point (°C): 57 Vapour Density (Air =1) : heavier vs. air</p>
---	--

SECTION IV - FIRE AND EXPLOSION DATA

<p>Flammability: Combustible LEL (% vol) lowest value of components: 0.7 UEL (% vol) highest value of components: 9.4 Hazardous Combustion Products: Carbon monoxide, Carbon dioxide, soot</p>	<p>Flash Point (°C TCC): 57</p>
---	--

Conditions of Flammability: Avoid heat, sources of ignition, static electricity, and electrical equipment. Keep containers closed. Containers may explode under extreme heat. Application to hot surfaces requires special precautions. Do not smoke near material.

Means of Extinction Fire: Carbon dioxide, foam, sand, chemical power. Water jet should not be used because water is not mixable with a lot of organic solvents.

Special Fire-Fighting Procedures: Clear area of unprotected personnel. Firefighters should wear NIOSH-approved, self-contained breathing apparatus (SCBA). Use water spray to cool fire-exposed surfaces. Also, use water to flush spilled material away from source. Vapours are harmful; stay upwind of a fire to minimize breathing of vapours, gases, fumes, or decomposition products being generated.

Unusual Fire & Explosion Hazards: Not explosive regarding sensitivity to mechanical impact. Solvent vapour in air may explode within flammable limits due to static discharge.

SECTION V - REACTIVITY DATA

<p>Stability: Stable Incompatibility: Strong acids, alkalis, or oxidizers Hazardous Decomposition Products: When exposed to high temperatures, carbon dioxide, carbon monoxide and soot can be produced.</p>

SECTION VI - TOXICOLOGICAL PROPERTIES

Routes of Entry: Eye, Skin, Inhalation, Ingestion

Effects of Acute Exposure:

Inhalation may cause head-ache, dizziness, tiredness, nausea. High concentration may cause vomiting, breathing difficulties, unconsciousness. Irritating and defatting effect on skin, danger of inflammation. Possibility of skin resorption. Irritating to eyes. With prolonged contact possibility of corneal opacity. Ingestion may cause nausea, indigestion, vomiting, diarrhea.

Effects of Chronic Exposure:

May effect liver, kidneys and central nervous system in case of repeated overexposure.

Irritancy: Vapour and the liquid itself will irritate the eyes

Sensitization: No

Carcinogenicity: no

Synergistic Materials: No data

Reproductive Effects: no

Teratogenicity: no

Mutagenicity: no

SECTION VII - PREVENTATIVE MEASURES

Gloves: Solvent impermeable gloves are required for repeated or prolonged contact.

Eye Protection: Wear safety glasses where contact with the eye is anticipated. Chemical safety goggles should be worn whenever there is a possibility of splashing or other contact with the eyes.

Respiratory Protection: Proper selection of respiratory protection depends upon many factors, including duration and level of exposure and conditions of use. In general, exposure to organic chemicals, such as those contained in this product, may not require the use of respiratory protection, if used in a well-ventilated area. In areas of restricted ventilation, a NIOSH approved organic vapour respirator may be required. Under certain conditions, such as spraying, a mechanical pre-filter may also be required. In confined areas, or in high exposure situations, a NIOSH/MSHA approved air-supplied respirator may be required. If the TLV's listed in Section II are exceeded, use a properly fitted NIOSH/MSHA approved respirator with an appropriate protection factor.

Use material only with adequate ventilation to prevent exceeding the recommended exposure limit or a build-up of explosive concentrations in the air. Use explosion proof equipment.

Other Protective Equipment Recommended: Eye wash station in the work area.

Engineering Controls: Use general dilution and local exhaust in sufficient volume, and pattern to keep concentrations of hazardous ingredients listed in Section II below the lowest exposure limit stated.

Leak and Spill Procedure:

Cover with humid liquid absorbing material (eg. sand or sawdust). After about one hour, take off into waste bin, but do not cover (carbon dioxide development). Keep damp and allow to stand in a secure area in the open air, for a few more days.

Waste Disposal: Review federal, provincial and local government requirements prior to disposal. Use a licensed waste treatment facility or reclaimer.

Storage Requirements: Store in a tightly closed container. Store away from incompatible materials. Store in a cool, dry, well-ventilated area. Avoid heating over 50 °C. Ensure all bottles are properly labeled.

Special Precautions: Ground all equipment to prevent static discharge. Keep containers away from heat, sparks, and open flame. Wash thoroughly with soap and water after handling material. Wash hands thoroughly before eating, drinking or using toilet facilities. Avoid contact with skin and eyes. Use re-greasing skin cream. Do not empty into drains.

SECTION VIII - FIRST AID

Effects of exposure (inhalation, ingestion or skin contact) to substance may be delayed. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

Take off all contaminated clothes.

Eye: Immediately flush eyes with a directed stream of water for at least 10-15 minutes, while holding eyelids open. Seek medical attention.

Skin: Flush affected areas with large amounts of water, remove contaminated clothing. Wash affected areas thoroughly with soap and water. Do not use solvents or thinner to wash! If irritation or redness develops or persists, get medical attention.

Inhalation: Remove victim to fresh air. If breathing difficulties develop, administer oxygen and get medical attention. If victim is not breathing, administer artificial respiration and get medical attention.

Ingestion: GET IMMEDIATE MEDICAL ATTENTION.

SECTION IX - PREPARATION AND ADDITIONAL INFORMATION

Prepared by: Sterling Marking Products Inc.
Quality Planning and Engineering Department
349 Ridout St., N.
London, Ontario N6A 2N8

Supersedes: June 16, 2011
Revision Date: March 28, 2012

Expires: 28-Mar-2015

Information for this material safety data sheet was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond the control of the supplier, it is assumed that user of this material has been fully trained according to the mandatory requirements of WHMIS. If user requires independent information on ingredients in this or any other material, we recommend contact with the Canadian Centre for Occupational Health and Safety (CCOHS) in Hamilton, Ontario (1-800-263-8276) or CSST in Montreal, Quebec (514-873-3990).